

COYO LIGHTING CO., LTD.

Email: sales@djstagelighting.com

Phone/WhatsApp: 0086-13760624745


Website: <http://www.coyolighting.com>

Address: No.6,Bajiang East Road, Private Business Industrial Park, Jianggao Town, Baiyun District, Guangzhou,510450 China



IP65 LED PAR Catalogue 2021

Item No.	Picture	Technical Specification
<p>OPAR18S</p> <p>NEW!</p> <p>18x10W RGBW Waterproof LED Par</p>		<p>Input voltage: AC100-240V, 50/60Hz Rated power: 180W/220W/280W Light source: 18x10W/12W/15W high power LEDs RGBW(RGBWA/RGBWA UV optional) Channel: 6/10/11 channels Dimming: 4 kinds of dimming curves adjustable LED PWM Frequency: 600Hz, 1200Hz, 2000Hz, 4000Hz, 12KHz, 25KHz adjustable Strobe: 0-30Hz Control: DMX512, master/save, auto, sound active Lens angle: 25° (15°, 40° optional) Display: OLED function menu with 4 buttons Dimming: 0-100%, 16bit dimming, flicker free Waterproof rating: IP65 Fixture Size: 29x16x37cm Packing Size: 32x20x39cm Net weight: 7KG Gross weight: 9KG Heat dissipation: intelligent temperature control, active</p>
<p>OPAR710</p> <p>NEW!</p> <p>7X10W RGBW Waterproof LED Par</p>		<p>Input voltage: AC100-240V, 50/60Hz Rated power: 80W/110W/130W Light source: 7x10W/15W/18W high power LEDs RGBW(RGBWA/RGBWA UV optional) Channel: 4/6/8 channels Dimming: 4 kinds of dimming curves adjustable LED PWM Frequency: 600Hz, 1200Hz, 2000Hz, 4000Hz, 12KHz, 25KHz adjustable Strobe: 0-30Hz Control: DMX512, master/save, auto, sound active Lens angle: 25° (15°, 40° optional) Display: OLED function menu with 4 buttons Dimming: 0-100%, 16bit dimming, flicker free Waterproof rating: IP65 Fixture Size: 23.5x23.5x19cm Packing Size: 25x25x23cm Net weight: 4.3kg Gross weight: 5.5KG</p>
<p>OPAR715</p> <p>IP65 Mini LED PAR 7x15W RGBWA+UV</p>		<p>Voltage: AC100-240V, 50/60Hz Power: 150W Light Source: RGBW: 7x10W RGBW 4in1 LED RGBWA: 7x12W RGBWA 5in1 LED RGBWA+UV: 7x15W RGBWA+UV 6in1 LED Dimming: 0-100%, 16bit dimming, flicker free operations Strobe: 0-20Hz Lifespan: around 50,000-100,000 hours DMX Channel: 6/10CH Control mode: DMX 512, Auto mode, Master/Slave, Sound mode Beam angle: 25° Waterproof Rating: IP65 N.W: 2.6KG Dimension: 175 x 12 x 225mm</p>

<p>OPAR630</p>		<p>Input voltage: AC100-240V, 50/60Hz Rated power: 180W Light source: 6x30W RGBWA 5in1 high power LEDs RGBW(RGBWA/RGBWA UV optional) LED Life time: over 50000hours Control mode: DMX512,Master/Slave, Auto Run,Sound active Channel: 4/8CH, 5/9CH,6/10H Dimmer: 0-100% linear dimming Strobe: 1-25times/sec Beam angle: 25° Waterproof Rate: IP65 Display: LED display Convention heat transfer cooling system without fan Packing Size: 40X29X23cm Net weight: 5KG Gross weight: 6KG</p>
<p>OPAR18D</p>		<p>Voltage: AC90-240V/50-60Hz Power consumption: 180W/270W/330W Light source: 18x18W(RGBWA+UV 6in1),18x15W(RGBWA 5in1) or 18x10W(RGBW 4IN1) High Power LEDs Control Channels: 4/8CH,5/9CH,6/10CH Operate Mode: Auto-run, Master/Slave,Sound-Active,DMX 512 Beam Angle: 25°/45°/60° Dimming: 0-100%,16bit dimming,flicker free operations Waterproof Rate: IP65 Connector: IP65 PowerCon in & out, IP65 DMX In & Out Net Weight: 7KG Weight: 8KG Package Size: 31x31x32cm</p>
<p>OPAR12B</p>		<p>Voltage: AC90-240V/50-60Hz Power consumption: 120W/180W/216W Light source: 12x18W(RGBWA+UV 6in1),18x15W(RGBWA 5in1) or 18x10W(RGBW 4IN1) High Power LEDs Control Channels: 4/8CH,5/9CH,6/10CH Operate Mode: Auto-run, Master/Slave,Sound-Active,DMX 512 Beam Angle: 25°/45°/60° Dimming: 0-100%,16bit dimming,flicker free operations Waterproof Rate: IP65 Connector: IP65 PowerCon in & out, IP65 DMX In & Out Net Weight:5.5KG Weight: 7KG Package Size: 31x31x32cm</p>
<p>OPAR54B</p>		<p>Voltage: AC90-240V/50-60Hz Power consumption: 180W Light source: 54PCS x 3W RGBW LEDs Beam Angle: 25°/45°/60° DMX Channels: 4/8CH Operate Mode: Auto-run, Master/Slave,Sound-Active,DMX 512 Dimming: 0-100%,16bit dimming,flicker free operations Waterproof Rate: IP65 Connector: IP65 PowerCon in & out, IP65 DMX In & Out Net Weight:5.5KG Weight: 7KG Package Size: 31x31x32cm</p>
<p>OPAR09</p>		<p>Voltage: AC90-240V/50-60Hz</p>

<p>9X18W Outdoor RGBWA+UV 6in1/RGBWA 5in1/RGBW 4in1 LED Par</p>		<p>Power consumption: 150W Light source: 9x18W(RGBWA+UV 6in1),9x15W(RGBWA 5in1) or 9x10W(RGBW 4IN1) High Power LEDs Control Channels: 10CH Operate Mode: Auto-run, Master/Slave,Sound-Active,DMX 512 Beam Angle: 25°/45°/60° Dimming: 0-100% linear dimming Waterproof Rate: IP65 Net Weight: 4.9KG Weight: 5.5KG Dimensions: 205*245*290 mm Package Size: 34x24x20cm</p>
<p>OPAR12A</p> <p>12X18W Outdoor RGBWA+UV 6in1/RGBWA 5in1/RGBW 4in1 LED Par</p>		<p>Voltage: AC90-240V/50-60Hz Power consumption: 120W/180W/270W Light source: 12x18W(RGBWA+UV 6in1),12x15W(RGBWA 5in1) or 12x10W(RGBW 4IN1) High Power LEDs Control Channels: 9CH/10CH/11CH Operate Mode: Auto-run, Master/Slave,Sound-Active,DMX 512 Beam Angle: 25°/45°/60° Dimming: 0-100% linear dimming Waterproof Rate: IP65 Net Weight: 5KG Weight: 6KG Dimensions: 15*245*290 mm Package Size: 27x28x39cm</p>
<p>OPAR14</p> <p>14X10W 4in1/5in1/6in1 Outdoor LED Par</p>		<p>Input voltage: AC1 00-240V 50/60HZ Consume: 260W/220W/150W LED Qty: 14x18W(RGBWA+UV 6in1),14x15W(RGBWA 5in1) or 14x10W(RGBW 4IN1) High Power LEDs Life span>50000~100000hours Control Signal: DMX512, Master/slave,sound activeted,auto run Channel: 4/5/6/10CH Function Effect:dimmer, strobe, eotic, gradual change,sound activeted Dimmer: 0-100% Beam Angle: 25°/45°/60° Optional Waterproof Rate: IP65 Weight: 4.5kg G.W.: 5.5KG Dimensions (WxHxD):245x245x205mm Package Size: 26x26x31cm</p>
<p>OPAR18A</p> <p>18x18/15/10W Outdoor RGBWA+UV 6in1/RGBWA 5in1/RGBW 4in1 LED PAR</p>		<p>Input voltage: AC100-240V 50/60HZ Power Consumption: 350W/280W/200W LED Qty: 18x18W(RGBWA+UV 6in1),18x15W(RGBWA 5in1) or 18x10W(RGBW 4IN1) High Power LEDs Life span>50000~100000hours Control Signal: DMX512, Master/slave,sound activeted,auto run Channel: 4/5/6/10CH Function Effect:dimmer, strobe, eotic, gradual change,sound activeted Dimmer: 0-100% Beam Angle: 25°/45°/60° Optional Waterproof Rate: IP65 Weight: 9KG Packing size: 33x33x38cm</p>
<p>OPAR18B</p>		

<p>18x10W/15W/18W RGBW 4in1 / RGBWA 5in1 / RGBWA+UV 6in1 Outdoor LED PAR</p>		<p>Input voltage: 100-240V/50-60 Hz Light source: 18x18W(RGBWA+UV 6in1),18x15W(RGBWA 5in1) or 18x10W(RGBW 4IN1) High Power LEDs Power Consumption: 350W/300W/200W Life span>50000~100000hours DMX Channels: 6/10CH Beam Angle: 25°/45°/60°Optional Function Effect:dimmer, strobe, eotic, gradual change,sound activeted Dimmer: 0-100% Rated IP 65 Outdoor Waterproof Size 230*305*276mm; Weight: 9KG Packing: Size: 30×30×37cm</p>
<p>OPAR18C</p> <p>18X18W Outdoor RGBWA+UV 6in1/RGBWA 5in1/RGBW 4in1 LED Par</p>		<p>Voltage: AC90-240V/50-60Hz Power consumption: 180W/270W/330W Light source: 18x18W(RGBWA+UV 6in1),18x15W(RGBWA 5in1) or 18x10W(RGBW 4IN1) High Power LEDs Control Channels: 6/11CH Operate Mode: Auto-run, Master/Slave,Sound-Active,DMX 512 Beam Angle: 25°/45°/60° Dimming: 0-100% linear dimming Waterproof Rate: IP65 Net Weight: 8.5KG Weight: 9KG Dimensions: 15*245*290 mm Package Size: 27x28x39cm</p>
<p>OPAR54A</p> <p>54X3W Outdoor RGBW LED Par Can</p>		<p>Voltage: AC90-240V/50-60Hz Power consumption: 200W Light source: 54PCS x 3W RGBW (Red 14 + Green 14 + Blue 14 + White 12) LEDs Beam Angle: 25°/45°/60° DMX Channels: 4/8CH Operate Mode: Auto-run, Master/Slave,Sound-Active,DMX 512 Waterproof Rate: IP 65 Shipping information Dimension: 350X230X290mm Packing: 300X300X360mm (1 pc) Packing: 620X320X390mm (2 pcs) Net weight: 8 kgs (1 pc) Gross weight: 9.5 kgs (1 pc)</p>
<p>Outdoor LED PAR ZOOM</p>		
<p>OPARZ1515</p> <p></p> <p>15x15W RGBW 4in1 LED PAR Zoom</p>		<p>Input voltage:AC100V-264V/47-63Hz Consumption:200W Light source:15X15W RGBW 4in1 LED Lifespan:50000-100000hours Driving current:700mA Control Signal:DMX512 Control mode:Stand alone, master/slaver, DMX mode, Sound activated Channel:5/9CH Beam Angle:10-40° Cooling mode:Natural Convection, built-in temperature control Protect rate:IP 65 Size:325x265x330mm Net Weight:10KG</p>

<p>OPARZ150</p>		<p>Power supply: AC100-240V,50Hz-60Hz, Power Consumption: 220W Light source: COB 150W White LED/RGBW 4in1 LED Controls: DMX512, Sound, Auto, Master/Slave DMX Channels: 2/3CH; 5/9CH Life time: 50000 hours Flash: up to 25 times Beam angle: 12-60° Control panel: Digital tube display screen Dimmer: 0-100% linearly adjustable Protection rate: Ip65 Case color: black/white Working environment: -20°C- 40°C Dimension size: 285×265x400mm Inner carton size:30*30*39cm; G.W:10KG Packing size:610×320×480mm (2pcs/ctn) G.W:19.8KG</p>
<p>OPARZ18</p>		<p>Voltage: AC90-240V/50-60Hz Power Consumption: 350W/300W/200W Light source: 18PCS x 18W/15/10W RGBWA+UV 6in1/RGBWA 5in1/RGBW 4in1 LEDs Operate Mode: Auto-run, Master/Slave,Sound-Active,DMX 512 Control Channels: 4/5/9/13CH ZOOM-Operating range: 8°to 40° motorized zoom° Protecting Grade:IP65 4 digital LED display-flip option Built-in 8 chases-w/fade,speed,strobe PWM speed: 1000Hz. Very good for digital camera and video recording. 16bit dimming,flicker free operations Strobe: Strobe effect(1-18 flashes per second) Net Weight: 8KG Gross Weight: 10KG Packing Size: 35x34x37cm</p>
<p>OPARZ24</p>		<p>Voltage: AC90-240V/50-60Hz Power Consumption: 350W/300W/200W Light source: 24PCS x 18W/15/10W RGBWA+UV 6in1/RGBWA 5in1/RGBW 4in1 LEDs Operate Mode: Auto-run, Master/Slave,Sound-Active,DMX 512 Control Channels: 4/5/9/13CH ZOOM-Operating range: 8°to 40° motorized zoom° Protecting Grade:IP65 4 digital LED display-flip option Built-in 8 chases-w/fade,speed,strobe PWM speed: 1000Hz. Very good for digital camera and video recording. 16bit dimming,flicker free operations Strobe: Strobe effect(1-18 flashes per second) Net Weight: 8KG Gross Weight: 10KG Packing Size: 35x34x37CM</p>